




MODEL:

HB-Series

Recessed Hose Box w/ Wall Flange

(Model# HB-8151 shown)

SPECIFICATIONS

HB-Series recessed Hose Box with Wall Flange shall be fabricated from Type 304 stainless steel, surfaces flush to the supporting wall, polished to a #4 satin finish.

Standard equipment shall include:

- 1/2" nominal brass valves and fittings
- Screwdriver stops on inlets

Inlets are 1/2" FIP; outlets are 3/4" MGHT.

MODELS AND OPTIONS*

HB-Series recessed hose boxes are available in single- or dual-temperature, with optional waste drains, vacuum breakers, and/or hinged doors (*Examples of 4 standard models on next page; see [HB-Series Spec Page](#) for complete listing).

INSTALLATION

1. Remove the Wall Flange and Hinged Door (if applicable) from the recessed Hose Box.
2. Select the mounting location for the Hose Box and frame/add backing based on the Hose Box dimensions (blocking, adequate backing, and framework by others).
3. Using the Wall Anchor Clips, mount the Hose Box centered and level within the recess so the opening is flush with the finished wall.
4. Connect the valve inlets to the correct supply connections and connect drain (as needed).
5. Test Hose Box and valves for leaks and to ensure proper operation.
6. Reinstall the Wall Flange using the included Anchoring Screws, and reattach the Hinged Door (if applicable) to the Wall Flange.



WILLOUGHBY

COUNT ON US.

1.800.428.4065 TOLL FREE | www.willoughby-ind.com



HB-SERIES HOSE BOX- STANDARD MODEL EXAMPLES

